

IRON SIGHT SLIDE FOR GLOCK® 19 GEN 3 - BROWNEllS IRON SIGHT SLIDE GEN3 GLOCK® 19 STAINLESS NITRIDE

[Handgun Parts](#) > [Slide Parts](#) > [Slides](#)

Perfect "Top Half" for a D.I.Y. Custom Pistol - Available with Window OR Wraparound Front Serrations

The Brownells Iron Sight Slide for Glock 19® Gen3 enables you to build a custom Glock®-style pistol with a slide that sports distinctive cocking serrations. The front serrations aid in manipulating the slide, especially for quick chamber checks AND for clearing the occasional jam (caused by problem ammo, of course!). Both the front and rear serrations are cut to the same depth as the Glock® factory slide serrations to ensure preservation of structural rigidity. The top edges and the front around the muzzle area are chamfered to reduce the risk of snagging on clothing and to make holstering the pistol easier. You can get your Brownells Iron Sight Slide for Glock® 19 Gen3 with a solid top and wraparound front cocking serrations OR a window cutout on top between the front side serrations. The window aids in heat dissipation to keep the barrel cool during extended fire. If you have an aftermarket barrel with a contrasting finish and / or fluting, spirals, "flames," or some other a unique exterior pattern, the window also shows off a bit of your pistol's bling. Accepts Gen3 Glock® 19 internal parts Factory cuts for iron sights Sturdy machined 17-4 stainless steel Hardened to Rockwell "C" 41-44 for superb wear resistance Durable, non-reflective matte Black Nitride finish Channel liner not included; please order separately (see note below) Window model available Like all Brownells slides, the Iron Sight model for Glock® 19 Gen3 is precision machined from solid 17-4 stainless steel billet to factory specifications inside so it is compatible with any factory or aftermarket Gen3 internal components. Outside, there's a Glock® factory rear sight dovetail and a standard Glock® front sight tenon cut ready for any factory or aftermarket sights you choose. This is the perfect companion "top-half" for a custom pistol built on a Polymer80 80% frame. Brownells Gun Tech™ Note: Channel liner required for these slides. Channel liner is a press fit and requires a tool to install. We recommend #777-100-017.



The Brownells Front Cut Slides for Glock® pistols allows any operator to build a custom Glock® style pistol from the ground up with a slide already customized with front slide serrations. Our Front Cut Slides feature a unique wraparound slide serration design that aids in weapon manipulation, especially when checking the chamber. Serrations are cut to the same depth as Glock® factory models to ensure lower slide rigidity. Models are also available with top window cutout between the front serrations. Slides start out as 17-4 stainless steel billet and are machined internally to factory specifications. Slides are compatible with any standard Glock® 17 or 19 components. The factory Glock® rear sight dovetail is machined, with a standard Glock® front sight cut at the front. Machined from 17-4 Stainless Steel Billet Heat treated & finished with a matte black nitride finish Factory internal dimensions Available for Glock® 17 or 19 pistols Available with a top window cutout at the front Factory Glock® sight cuts For Gen3 pistols Improve the functionality and performance of your Glock® 17 or 19 with the Brownells Front Cut Slides. Channel liner required for these slides. Channel liners are a press fit and require a tool to install.

Attributes

- Name: [BROWNELLS IRON SIGHT SLIDE GEN3 GLOCK® 19 STAINLESS NITRIDE](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 078000367
- Mfr. No.: NONE
- Cartridge: 9 mm Luger
- Finish: Black
- Model: 19
- Sights: Dovetail
- Style: Front & Rear Serrations
- Weapon type: Glock
- Delivery weight: 0.227kg
- Shipping height: 38mm
- Shipping width: 38mm
- Shipping length: 191mm
- UPC: 050806112551

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- Startpage
- Safety Instruction Guide for Brownells Iron Sight Slide for Glock® 19 Gen 3
- About Us

Safety Instruction Guide for Brownells Iron Sight Slide for Glock® 19 Gen 3

Introduction

Thank you for choosing the Brownells Iron Sight Slide for Glock® 19 Gen 3. This product is designed to enhance your shooting experience while ensuring safety during use. Please read this safety instruction guide carefully to understand how to use, install, and dispose of the product safely.

General Safety Guidelines

- Always treat every firearm as if it is loaded.
- Ensure that the firearm is pointed in a safe direction at all times.
- Keep your finger off the trigger until you are ready to shoot.
- Store the firearm and its components in a secure location, out of reach of children and unauthorized users.
- Be aware of your surroundings and ensure that you are in a safe and appropriate environment for shooting.
- Regularly inspect the slide and other components for any signs of wear or damage.
- Follow all local laws and regulations regarding firearms and their components.

Specific Safety Precautions for Use

- Ensure that the Brownells Iron Sight Slide is compatible with your Glock® 19 Gen 3 before installation.
- Use only factory or compatible aftermarket parts when assembling your firearm.
- If you experience any malfunctions, such as jams or misfires, follow proper clearing procedures and do not attempt to fire the weapon again until the issue is resolved.
- Avoid using reloaded or damaged ammunition, as this can cause malfunctions and potentially harm the user.
- Always wear appropriate eye and ear protection when shooting.
- Do not modify the slide or any of its components beyond manufacturer specifications.

Instructions for Installation and Usage

1. Preparation:

- Ensure that the firearm is unloaded and the magazine is removed.
- Gather all necessary tools for installation, including a channel liner installation tool (recommended: #777100017).

2. Installation:

- Remove the existing slide from your Glock® 19 Gen 3.
- Install the channel liner into the new Brownells Iron Sight Slide. Ensure it is a secure press fit.
- Attach the slide to the frame of the Glock® 19 Gen 3, ensuring that it is properly aligned.
- Install the factory or aftermarket sights onto the slide, ensuring they are securely fastened.

3. Usage:

- Ensure that the firearm is properly assembled and that all components are functioning correctly before use.
- Conduct a function check to confirm that the slide operates smoothly and that the safety features are engaged.

- When ready to shoot, load the firearm with compatible ammunition and follow standard shooting practices.

Disposal Instructions

- Dispose of the Brownells Iron Sight Slide in accordance with local regulations regarding firearm components.
- Do not dispose of any part of the slide in regular household waste.
- If the slide is damaged or no longer usable, consider contacting a local firearms dealer for safe disposal options.

Contact Information for Further Support

For any inquiries regarding safety or product support, please refer to the manufacturer's contact points, which can be found on the product packaging or the official website.

Please remember to always prioritize safety when handling firearms and their components. Regular training and adherence to safety guidelines will enhance your shooting experience while ensuring the safety of yourself and others.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk