

EXTRACTOR W/LOADED CHAMBER, NEW STYLE, 9MM

[Handgun Parts](#) > [Action Parts](#) > [Extractor Parts](#) > [Extractors](#)

FITS: Model 17, 9mm; Model 19, 9mm; Model 26, 9mm; Model 34, 9mm

Extractor 9mm, .380 (15o) with Loaded Chamber Indicator (LCI) (use only with 2714 Bearing)



Attributes

- Name: [EXTRACTOR W/LOADED CHAMBER, NEW STYLE, 9MM](#)
- Manufacturer: [GLOCK](#)
- Product no.: 100002712
- Mfr. No.:
- Caliber: 9 mm (.355-.356)
- Finish: Blued
- Make: Glock
- Model: 17,19,26,34
- Delivery weight: 0.005kg
- Shipping height: 3mm
- Shipping width: 56mm
- Shipping length: 97mm

Item details

US export classification: 0A501.x

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for EXTRACTOR W/LOADED CHAMBER, NEW STYLE, 9MM](#)
- [About Us](#)

Safety Instruction Guide for EXTRACTOR W/LOADED CHAMBER, NEW STYLE, 9MM

Introduction

Thank you for choosing the EXTRACTOR W/LOADED CHAMBER, NEW STYLE, 9MM. This product is designed to provide reliable performance and safety during use. Please read this safety instruction guide carefully to ensure proper handling and maintenance of the extractor.

General Safety Guidelines

- Always handle the extractor with care and follow all safety instructions.
- Ensure that the extractor is compatible with your firearm model (Glock 17, 19, 34, 26).
- Store the extractor in a secure location, away from children and unauthorized users.
- Regularly check for any signs of wear or damage and replace if necessary.
- Keep the extractor clean and free from obstructions to ensure proper function.

Specific Safety Precautions for Use

- Use only with the specified 2714 Bearing to avoid malfunctions.
- Always verify that the firearm is unloaded before installing or removing the extractor.
- Do not attempt to modify or alter the extractor in any way.
- Wear appropriate safety gear, such as eye protection, when handling the extractor.
- Be aware of your surroundings and ensure that you are in a safe environment when using the extractor.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded.
- Remove the slide from the firearm according to the manufacturer's instructions.
- Locate the extractor housing and remove the old extractor if applicable.
- Carefully insert the new extractor into the housing, ensuring it is seated properly.
- Reassemble the slide and ensure it functions correctly before use.

2. Usage:

- Always follow the manufacturer's guidelines for your specific firearm model.
- Regularly inspect the extractor for proper function and wear.
- If the extractor fails to function correctly, cease use immediately and consult a qualified gunsmith.

Disposal Instructions

- Dispose of the extractor in accordance with local regulations for hazardous materials.
- Do not dispose of the extractor in regular household waste.
- Contact your local waste management facility for guidance on proper disposal methods.

Contact Information for Further Support

For safety inquiries or additional support regarding the EXTRACTOR W/LOADED CHAMBER, NEW STYLE, 9MM, please refer to the manufacturer's website or customer service resources.

Conclusion

By following these safety instructions, you can ensure the safe and effective use of the EXTRACTOR W/LOADED CHAMBER, NEW STYLE, 9MM. Always prioritize safety and compliance with all guidelines to protect yourself and others. Thank you for your attention to these important safety measures.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at