

RIFLE BULLET MOULD .314 200 GRAIN - LYMAN DOUBLE CAVITY MOULDS .303 CAL .314 DIA. 200 GR.

Lyman rifle moulds are the standard by which all other rifle moulds are judged. All Lyman rifle moulds are available in double cavity only, except those moulds where the size of the bullet necessitates a single cavity. All rifle moulds shown below require double cavity handles, regardless of the number of cavities indicated.



Attributes

- Name: LYMAN DOUBLE CAVITY MOULDS .303 CAL .314 DIA. 200 GR.
- Manufacturer: LYMAN
- Product no.: 250021116
- Mfr. No.: 2660299
- Bullet Weight (Grains): 200
- Caliber: 303 Caliber
- Diameter (in): 0.314
- Delivery weight: 0.454kg
- Shipping height: 51mm
- Shipping width: 51mm
- Shipping length: 108mm
- UPC: 011516202994

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: Safety Instruction Guide for LYMAN RIFLE BULLET MOULD .314 200 GRAIN](#)

Safety Instruction Guide for LYMAN RIFLE BULLET MOULD .314 200 GRAIN

Introduction

Thank you for choosing the LYMAN RIFLE BULLET MOULD .314 200 GRAIN. This product is designed for safe and effective use in bullet casting. To ensure your safety and the safety of others, please read and follow these safety instructions carefully. This guide is compliant with the EU General Product Safety Regulation (GPSR) and aims to provide you with the necessary information for safe usage.

General Safety Guidelines

- Always read and understand the product manual before use.
- Keep the mould out of reach of children and vulnerable individuals.
- Use the mould only for its intended purpose.
- Inspect the mould for any damages or defects before each use.
- Use appropriate personal protective equipment (PPE) such as gloves and safety goggles.
- Ensure that your workspace is clean, wellventilated, and free from hazards.
- Report any unsafe products or accidents to the relevant authorities.
- Check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the mould is securely attached to the handles before use.
- Avoid using the mould near flammable materials or in areas with poor ventilation.
- Do not exceed the recommended temperature limits when melting lead or other materials.
- Handle hot materials and equipment with care to prevent burns or injuries.
- Never leave the mould unattended while in use.
- Allow the mould to cool down completely before handling or cleaning.
- Use caution when removing bullets from the mould to avoid injury.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools and materials, including the LYMAN RIFLE BULLET MOULD, handles, and a heat source.
- Ensure your workspace is clean and organized.

2. Installation:

- Attach the mould to the double cavity handles securely.
- Ensure that the mould is properly aligned and locked in place.

3. Usage:

- Preheat the mould according to the manufacturer's recommendations.
- Melt the lead or other materials in a safe and controlled environment.
- Carefully pour the melted material into the mould cavities.
- Allow the material to cool and solidify as per the recommended time.
- Gently open the mould and remove the bullets.

4. PostUsage:

- Clean the mould thoroughly after each use to prevent buildup.
- Store the mould in a safe, dry place away from children and pets.

Disposal Instructions

- Dispose of any unused or damaged moulds in accordance with local regulations.
- Do not throw the mould in regular household waste.
- Check with local waste management authorities for proper disposal methods.

Contact Information for Further Support

For further support or inquiries regarding safety or product issues, please refer to the manufacturer's contact information provided with the product packaging.

By following these safety instructions, you can ensure a safe and effective experience while using the LYMAN RIFLE BULLET MOULD .314 200 GRAIN. Thank you for your attention to safety, and enjoy your casting experience!