

WINCHESTER XPR LONG ACTION PICATINNY SCOPE MOUNT - EGW

WINCHESTER XPR LA 1-PIECE PICATINNY BASE 0 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

This mount comes standard with a bevel on both sides making it ambidextrous. EGW recommends measuring the hole spacing in your receiver to confirm it matches with the dimensions they have published. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The channel in the center reduces the overall mass of the mount. Also, in many cases, it will not obstruct usage of factory iron sights. Their one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. They machine these in their shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type II anodized for long lasting durability.

Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately). They recommend: 0 MOA - if shooting 0-500 yards 20 MOA - if shooting 500-1000 yards When zeroing your rifle with a 20 MOA mount, they recommend zeroing at 200 yards. The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA.



Attributes

- Name: [EGW WINCHESTER XPR LA 1-PIECE PICATINNY BASE 0 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000616
- Mfr. No.: 42600
- Action Type: Long
- Colour: Black
- Elevation: 0 MOA
- Material: Aluminum
- Model: XPR
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Winchester
- Delivery weight: 0.091kg
- Shipping height: 25mm
- Shipping width: 102mm
- Shipping length: 229mm
- UPC: 841370114023

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for WINCHESTER XPR LONG ACTION PICATINNY SCOPE MOUNT
- About Us

Safety Instruction Guide for WINCHESTER XPR LONG ACTION PICATINNY SCOPE MOUNT

Introduction

Thank you for choosing the WINCHESTER XPR LONG ACTION PICATINNY SCOPE MOUNT. This guide provides essential safety instructions and guidelines to ensure safe and effective use of the product. Please read this document carefully before installation and usage.

General Safety Guidelines

- **Product Safety:** Ensure safe use of this scope mount by following the instructions provided. This product is designed for nonfood use and complies with EU safety standards.
- **Enhanced Recalls:** Stay informed about product recalls. If you receive a recall notice, follow the instructions provided for safe return or remedy.
- **Online Shopping Safety:** If purchased online, ensure that the seller complies with safety regulations similar to physical stores.
- **Consumer Focus:** Special care should be taken when the product is used by or around vulnerable groups, including children.
- **Report Unsafe Products:** If you encounter an unsafe product or experience an accident, report it to the relevant authorities immediately.
- **Check for Updates:** Regularly check the EU's Safety Gate platform for any recall updates or safety alerts.

Specific Safety Precautions for Use

- **Avoid OverTightening:** When installing the mount, do not exceed the recommended torque of 20 inch lbs to prevent damage.
- **Use Blue Loctite:** Apply a drop of blue loctite to the screws during installation to ensure secure fastening. Loctite is sold separately.
- **Confirm Compatibility:** Measure the hole spacing in your receiver to ensure compatibility with the mount dimensions.
- **Inspect Before Use:** Regularly inspect the mount for any signs of wear or damage before use.
- **Use in Appropriate Conditions:** Ensure that the mount is used in conditions suitable for its design, avoiding extreme temperatures or moisture that could affect performance.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a torque wrench and a drop of blue loctite.
- Ensure the rifle and scope are clean and free of debris.

2. Installation:

- Align the mount with the receiver holes.
- Insert the screws into the mount and receiver holes.
- Tighten the screws to a torque of 20 inch lbs using the torque wrench.
- Apply a drop of blue loctite to each screw before final tightening.

3. Zeroing the Scope:

- If using a 20 MOA mount, it is recommended to zero your rifle at 200 yards.

- Adjust the scope as necessary to achieve the desired accuracy for your shooting range.

4. Usage:

- Always ensure that the mount is securely fastened before each use.
- Monitor the mount during use for any signs of loosening or damage.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the scope mount and packaging materials in accordance with local regulations.
- **Recycling:** If possible, recycle aluminum and other materials according to your local recycling guidelines.

Contact Information for Further Support

For any inquiries or support regarding the WINCHESTER XPR LONG ACTION PICATINNY SCOPE MOUNT, please refer to the manufacturer's website or contact their customer support for assistance.

By following these guidelines, you can ensure safe and effective use of your WINCHESTER XPR LONG ACTION PICATINNY SCOPE MOUNT. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk