

WINCHESTER XPR SHORT ACTION PICATINNY SCOPE MOUNT - EGW

WINCHESTER XPR SA 1-PIECE PICATINNY BASE 0 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

This mount comes standard with a bevel on both sides making it ambidextrous. EGW recommends measuring the hole spacing in your receiver to confirm it matches with the dimensions they have published. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The channel in the center reduces the overall mass of the mount. Also, in many cases, it will not obstruct usage of factory iron sights. Their one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. They machine these in their shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type II anodized for long lasting durability.

Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately). They recommend: 0 MOA - if shooting 0-500 yards 20 MOA - if shooting 500-1000 yards When zeroing your rifle with a 20 MOA mount, they recommend zeroing at 200 yards. The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA.



Attributes

- Name: [EGW WINCHESTER XPR SA 1-PIECE PICATINNY BASE 0 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000618
- Mfr. No.: 42603
- Action Type: Short
- Colour: Black
- Elevation: 0 MOA
- Material: Aluminum
- Model: XPR
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Winchester
- Delivery weight: 0.091kg
- Shipping height: 25mm
- Shipping width: 102mm
- Shipping length: 229mm
- UPC: 841370114597

Item details

Made in USA

Table of Contents

- Startpage
- WINCHESTER XPR SHORT ACTION PICATINNY SCOPE MOUNT SAFETY INSTRUCTIONS
- About Us

WINCHESTER XPR SHORT ACTION PICATINNY SCOPE MOUNT SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the WINCHESTER XPR Short Action Picatinny Scope Mount. This guide provides essential safety instructions, installation guidance, and usage recommendations to ensure your product is used safely and effectively.

General Safety Guidelines

- **Product Safety:** Ensure you understand the safe use of this scope mount. Follow all instructions carefully to avoid accidents.
- **Enhanced Recalls:** Stay informed about any product recalls. If you receive a recall notice, follow the instructions provided.
- **Online Shopping:** If you purchased this product online, ensure that the seller complies with safety requirements.
- **Special Consumer Focus:** This product is not intended for children. Keep it out of reach of minors.
- **EU Contact Point:** For any safety inquiries, refer to the designated EU contact point for this product.
- **Rapid Alerts:** Monitor the EU's Safety Gate platform for updates on any unsafe products.

Specific Safety Precautions for Use

- **Inspection:** Before installation, inspect the scope mount for any damage or defects. Do not use if damaged.
- **Compatibility:** Verify that this mount is compatible with your rifle model to prevent any installation issues.
- **Torque Specifications:** Use a torque wrench set to 20 inch lbs when tightening screws to ensure proper installation.
- **Loctite Application:** Apply a drop of blue Loctite to screws during installation to prevent loosening. Loctite is sold separately.
- **Zeroing:** When using a 20 MOA mount, zero your rifle at 200 yards for optimal performance.
- **Iron Sights:** The mount is designed to not obstruct factory iron sights in most cases. Ensure proper alignment before use.

Instructions for Installation and Usage

1. Preparation:

- Gather necessary tools: torque wrench, appropriate screwdriver, and blue Loctite.
- Ensure your rifle is unloaded and pointed in a safe direction.

2. Installation:

- Measure the hole spacing in your receiver to confirm compatibility with the mount dimensions.
- Align the mount with the holes on your rifle receiver.
- Insert the screws through the mount into the receiver holes.
- Tighten the screws using a torque wrench to 20 inch lbs.
- Apply a drop of blue Loctite to each screw to secure them in place.

3. Usage:

- Attach your scope rings and other accessories as needed using the Picatinny cross slots.

- Ensure all accessories are securely mounted before using the rifle.
- Regularly check the tightness of the screws and the condition of the mount.

Disposal Instructions

- Dispose of this product in accordance with local regulations.
- Do not dispose of with household waste. Check for local recycling programs that accept aluminum materials.

Contact Information for Further Support

For additional support or inquiries regarding safety, installation, or usage of the WINCHESTER XPR Short Action Picatinny Scope Mount, please refer to the designated EU contact point.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk