

WINCHESTER XPR SHORT ACTION PICATINNY SCOPE MOUNT - EGW

WINCHESTER XPR SA 1-PIECE PICATINNY BASE 20 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

This mount comes standard with a bevel on both sides making it ambidextrous. EGW recommends measuring the hole spacing in your receiver to confirm it matches with the dimensions they have published. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The channel in the center reduces the overall mass of the mount. Also, in many cases, it will not obstruct usage of factory iron sights. Their one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. They machine these in their shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type II anodized for long lasting durability.

Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately). They recommend: 0 MOA - if shooting 0-500 yards 20 MOA - if shooting 500-1000 yards When zeroing your rifle with a 20 MOA mount, they recommend zeroing at 200 yards. The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA.



Attributes

- Name: [EGW WINCHESTER XPR SA 1-PIECE PICATINNY BASE 20 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000619
- Mfr. No.: 42604
- Action Type: Short
- Colour: Black
- Elevation: 20 MOA
- Material: Aluminum
- Model: XPR
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Winchester
- Delivery weight: 0.088kg
- Shipping height: 19mm
- Shipping width: 89mm
- Shipping length: 229mm
- UPC: 841370114603

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for WINCHESTER XPR Short Action Picatinny Scope Mount
- About Us

Safety Instruction Guide for WINCHESTER XPR Short Action Picatinny Scope Mount

Introduction

Thank you for choosing the WINCHESTER XPR Short Action Picatinny Scope Mount. This guide provides important safety instructions and usage guidelines to ensure safe and effective use of your product. Please read this document carefully before installation and use.

General Safety Guidelines

- Product Safety: Always ensure the safe use of the scope mount. Improper installation or use may lead to accidents or injuries.
- Enhanced Recalls: Stay informed about any recall notices related to this product. Check the EU's Safety Gate platform for updates.
- Online Shopping: When purchasing online, ensure that the seller complies with safety requirements.
- Special Consumer Focus: Extra care should be taken when the product is used by or around vulnerable groups, such as children.
- EU Contact Point: For any safety inquiries, please ensure to reach out to the designated EU contact for assistance.
- Rapid Alerts: Be aware of the Safety Gate system for rapid updates on unsafe products.

Specific Safety Precautions for Use

- Always inspect the scope mount before installation for any visible damage or defects.
- Ensure that the mount is compatible with your firearm by measuring the hole spacing in your receiver.
- Use the recommended torque of 20 inch lbs when securing the mount to prevent loosening during use.
- Apply a drip of blue Loctite to the mounting screws to ensure they stay secure. (Loctite is sold separately.)
- Avoid using the mount if you notice any unusual wear or if the mount obstructs factory iron sights.
- Always ensure that the firearm is unloaded before installing or adjusting the scope mount.

Instructions for Installation and Usage

1. Preparation

- Gather the necessary tools: a torque wrench and a drip of blue Loctite.
- Ensure that your firearm is unloaded and in a safe position.

2. Measuring Hole Spacing

- Measure the hole spacing in your receiver to confirm compatibility with the scope mount dimensions published by EGW.

3. Installation Steps

- Align the scope mount over the holes on your receiver.
- Insert the mounting screws through the holes of the mount into the receiver.
- Use the torque wrench to tighten the screws to the recommended torque of 20 inch lbs.
- Apply a drip of blue Loctite to each screw to secure them in place.

4. Zeroing the Mount

- When using a 20 MOA mount, it is recommended to zero your rifle at 200 yards.
- Adjust your scope accordingly for optimal accuracy at your desired shooting distance.

5. Final Checks

- After installation, doublecheck that all screws are tightened and the mount is securely attached to the firearm.
- Ensure that the mount does not obstruct the use of factory iron sights.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the scope mount in household waste.
- Consider recycling materials where possible.

Contact Information for Further Support

For assistance, please reach out to the designated EU contact for safety inquiries regarding the WINCHESTER XPR Short Action Picatinny Scope Mount.

By following this guide, you will ensure safe and effective use of your scope mount. Thank you for prioritizing safety and compliance with the EU General Product Safety Regulation.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk