

RMR TYPE 2 RM06 ADJUSTABLE LED REFLEX SIGHT - RMR TYPE 2 RM06 3.25 MOA RED DOT SIGHT BLACK

[Optics & Mounting](#) > [Electronic Sights](#) > [Reflex Sights](#)

RMR TYPE 2 RM06 3.25 MOA ADJUSTABLE LED REFLEX SIGHT The RMR Type 2 is designed with a patented housing shape that absorbs impacts and diverts stresses away from the lens to increase durability. It also offers redesigned and upgraded electronics that have been proven to perform when mounted on slide ride pistols and other small arms. It's suitable for military, law enforcement, concealed carry self-defense, target shooting, and hunting applications. The RMR® Type 2 Adjustable LED sight puts the illumination control in the user's hands. Easy-to-use buttons on the sides of the optic allow the user to adjust the illumination brightness, toggle between manual and automatic modes, and power down the RMR for storage. The automatic mode functions the same as the LED RMR version. If a manual mode has been chosen, the RMR will remain in manual mode for 16.5 hours following the last push of a button. After 16.5 hours, the optic will default back to the automatic mode so that the RMR will be ready for your next mission or task. All RMR Type 2 Adjustable LED sights are compatible with night vision devices, with the 3.25 MOA dot size being the most popular. Additionally, the user can also lock out the buttons so that the RMR functions in automatic mode only. This ensures that inadvertent button pushes do not cause a loss of aiming solution. The 3.25 MOA dot in the RM06 is the most versatile and popular of all RMR dot sizes. The dot is small enough to allow accurate shooting at range while also being big enough to locate quickly.

FEATURES:

- OUTSTANDING DURABILITY** Unique, patented housing shape diverts the force of an impact away from the lens, greatly increasing durability.
- DUAL-ILLUMINATED OPTION** Tritium-phosphor lamp illuminates reticle in low-light conditions and fiber optics automatically adjust the brightness level and contrast to available light conditions.
- BUILT TO HANDLE THE WORST** Designed to be waterproof to 20 meters (66 ft.)
- BATTERY CONSERVATION MODE** Automatically adjusts aiming dot to ambient lighting conditions after 16.5 hours (Automatic LED & Adjustable LED RMR only).
- TRUE-COLOR, MULTI-COATED LENS** Creates a wide-band light transmission for minimal change in target area color.
- ADJUSTABLE LED OPTION** Easy-to-use buttons on the sides of the optic allow the user to adjust the illumination brightness, toggle between manual and automatic modes, and power down the RMR® for storage.
- EASILY ADJUSTABLE WINDAGE/ELEVATION** No need for special tools. 1 MOA per click.

MULTI-PLATFORM-FRIENDLY Multiple primary applications including rifle, pistol, shotgun and carbine, or use as a secondary sight with a magnified optic.

UPGRADED ELECTRONICS Ruggedized battery contacts and electronics ensure performance and survivability in harsh environments (Automatic LED & Adjustable LED RMR only).

SPECIFICATIONS:

- Length x Width x Height: 1.8 in x 1.1 in x 1. in (45.72mm x 27.94mm x 25.4mm)
- Weight: 1.2 oz. (34.02g)
- Magnification: 1x
- Reticle Pattern: 3.25 MOA Dot
- Bullet Drop Compensating (BDC): No
- Bindon Aiming Concept™ (BAC): No
- Illumination Source: LED
- Power Source: CR2032 Lithium Battery
- Battery Life: Over 4 years of continuous use (when used at 70°F (21°C) at setting 4 of 8. *Extreme temperatures (high or low) will affect lithium battery performance.
- Adjustment: 1 MOA Per Click
- Housing Material: Forged Aluminum
- Finish: Matte Black

NOTE: The RMR® Type 2 has identical physical dimensions and mounting footprint to that of the original RMR Type 1. If selecting an RMR for mounting on the Glock® MOS, Springfield® OSP, Walther® PDP, or H&K® VP9



Optics Ready, a Trijicon RMR® mounting kit (AC32064) is required.

Attributes

- Name: [RMR TYPE 2 RM06 3.25 MOA RED DOT SIGHT BLACK](#)
- Manufacturer: [TRIJICON](#)
- Product no.: 892000321
- Mfr. No.: 700672
- Battery Life: 4 yrs
- Brightness Settings: 8 settings
- Click Value: 1 MOA
- Click Value: 1 MOA
- Finish: Black
- Night Vision Compatible: No
- Night Vision Compatible: No
- Power Supply: (1) CR 2032 Lithium battery
- Reticle: 3.25 MOA red dot
- Weight: 1.2 oz
- Delivery weight: 0.386kg
- Shipping height: 89mm
- Shipping width: 127mm
- Shipping length: 140mm
- UPC: 719307614239

Item details

Made in USA

US export classification: 0A504.c

Table of Contents

- Startpage
- RMR TYPE 2 RM06 3.25 MOA ADJUSTABLE LED REFLEX SIGHT Safety Instruction Guide
- About Us

RMR TYPE 2 RM06 3.25 MOA ADJUSTABLE LED REFLEX SIGHT Safety Instruction Guide

Introduction

Thank you for choosing the Trijicon RMR TYPE 2 RM06 3.25 MOA Adjustable LED Reflex Sight. This guide provides important safety information and instructions to ensure the safe and effective use of your reflex sight. Please read this manual carefully before using the product.

General Safety Guidelines

- Ensure that the sight is compatible with your weapon before installation.
- Always handle firearms and accessories safely and responsibly.
- Use the sight only for its intended purpose as described in this manual.
- Be aware of your surroundings and ensure a clear line of sight when aiming.
- Regularly check the sight for any signs of wear or damage.
- Always keep the sight clean and free from obstructions.

Specific Safety Precautions for Use

- Do not use the sight if it is damaged or malfunctioning.
- Avoid exposing the sight to extreme temperatures or harsh environmental conditions.
- Keep the sight away from children and unauthorized users.
- Do not attempt to disassemble or repair the sight yourself.
- Always ensure that the weapon is unloaded when attaching or detaching the sight.
- Use appropriate eye protection when using the sight.

Instructions for Installation and Usage

1. Installation:

- Ensure the weapon is unloaded.
- Attach the RMR sight to the mounting platform securely.
- Tighten the screws to the manufacturer's specifications to avoid loosening during use.
- Verify that the sight is properly aligned with the weapon's barrel.

2. Usage:

- To power on the sight, press the plus button.
- Adjust the brightness using the plus and minus buttons.
- For autoadjust mode, press both buttons simultaneously and release.
- To turn off the sight, press both buttons simultaneously and hold for 3 seconds.
- Make windage and elevation adjustments using the audible click adjusters.

Disposal Instructions

- Dispose of the sight in accordance with local regulations.
- Remove the battery before disposal and recycle it according to local battery recycling programs.
- Do not dispose of the sight in household waste.

Contact Information for Further Support

For any safety inquiries or support regarding the Trijicon RMR TYPE 2 RM06 3.25 MOA Adjustable LED Reflex Sight, please refer to the manufacturer's contact information provided separately.

Conclusion

By following these safety guidelines and instructions, you can ensure the safe and effective use of your Trijicon RMR TYPE 2 RM06 3.25 MOA Adjustable LED Reflex Sight. Always prioritize safety and responsibility when handling firearms and related accessories. Thank you for your attention to these important safety measures.

About Us

Brownells Deutschland

**Brownells Deutschland - Einer der größten Lieferanten für Waffenteile,
Büchsenmacherwerkzeug & Schießsportzubehör**

Lahnstraße 1
24539 Neumünster
Deutschland

www.brownells-deutschland.de