

TL Rear Sight for LLV

[Handgun Parts](#) > [Sights](#) > [Rear Sights](#)

TL Rear Sight for LLV



Precision-machined to ensure accurate, repeatable click adjustments for windage and elevation. No fitting required. Uses factory dovetail and locksin place with two set screws. Made of steel. Rear sight notch width is 0.110".

Please note that rear sight height differs between our LLV and factory Ruger uppers so be sure to order the correct item.

Attributes

- Name: [TL Rear Sight for LLV](#)
- Manufacturer: [VOLQUARTSEN](#)
- Product no.: BRD231077
- Mfr. No.: VC2TL-H
- Color: Black
- Make: Ruger
- Model: LLV, Scorpion, Black Mamba uppers
- Delivery weight: 0.4kg
- UPC: 810162014711

Table of Contents

- Startpage
- TL Rear Sight for LLV Safety Instruction Guide
- About Us

TL Rear Sight for LLV Safety Instruction Guide

Introduction

Thank you for choosing the TL Rear Sight for LLV. This guide provides essential safety instructions, usage guidelines, and installation procedures to ensure the safe and effective use of your new rear sight. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that the TL Rear Sight is compatible with your firearm model. This product is designed for Ruger LLV, Scorpion, and Black Mamba uppers.
- Always handle your firearm safely and responsibly. Follow all local laws and regulations regarding firearm usage.
- Keep the rear sight and all firearm components out of reach of children and unauthorized users.
- Regularly inspect the rear sight for any signs of wear or damage. Do not use if damaged.
- If you experience any issues with the rear sight, discontinue use immediately and seek professional assistance.

Specific Safety Precautions for Use

- Ensure that the firearm is unloaded before installing or adjusting the rear sight.
- Use caution when making adjustments to the windage and elevation settings to avoid unintentional changes.
- Do not attempt to modify or alter the rear sight in any way. Unauthorized modifications may compromise safety and performance.
- Always wear appropriate eye protection when shooting.
- Be aware of your surroundings and ensure a safe shooting environment.

Instructions for Installation and Usage

1. Preparation

- Ensure that your firearm is unloaded and pointed in a safe direction.
- Gather necessary tools: a screwdriver suitable for the set screws.

2. Installation

- Locate the factory dovetail on your Ruger upper.
- Align the TL Rear Sight with the dovetail and gently slide it into place.
- Secure the rear sight by tightening the two set screws. Ensure they are snug but do not overtighten to avoid damage.

3. Adjustments

- To adjust windage, use the appropriate tool to turn the adjustment screw clockwise or counterclockwise as needed.
- For elevation adjustments, similarly turn the designated screw to raise or lower the sight.
- Make small adjustments and test the sighting before making further changes.

4. Post-Installation Check

- After installation, doublecheck that the rear sight is securely fastened.
- Confirm that all adjustments are functioning properly before using the firearm.

Disposal Instructions

- Dispose of the TL Rear Sight in accordance with local regulations regarding metal and firearm accessory disposal.
- Do not dispose of in regular household waste. Check with local authorities for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the TL Rear Sight for LLV, please refer to the manufacturer's website or contact your retailer for assistance. Always ensure that you have the latest updates on safety recalls and product information.

Thank you for your attention to these safety instructions. Your safety and the safe use of your firearm are of utmost importance. Enjoy your shooting experience with the TL Rear Sight for LLV.

About Us

Brownells Deutschland

**Brownells Deutschland - Einer der größten Lieferanten für Waffenteile,
Büchsenmacherwerkzeug & Schießsportzubehör**

Lahnstraße 1
24539 Neumünster
Deutschland

www.brownells-deutschland.de