

6-36x56 PM II High Performance - 6-36x56 PM II High Performance LPI TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 6-36×56 PM II High Performance from Schmidt and Bender is a benchmark optic engineered for serious medium- to extreme-long-range shooting. With its expansive 6–36× magnification range and a generous 56 mm objective lens, it delivers exceptional clarity, reach and flexibility for demanding applications.

Crafted on a robust 34 mm main tube, the scope is compact in length (approx. 390 mm) and relatively light for its class (around 940 g), yet built with the ruggedness and precision befitting the PM II series. The first-focal-plane (FFP) reticle ensures accurate hold-overs, ranging and subtensions at every magnification level. With a transmission rating of well over 90 %, the optical system offers bright, high-resolution imagery critical for target recognition at extended distances.

Its field of view spans about 7.3–1.3 m @100 m, and the exit pupil ranges from approximately 8.3–1.6 mm, providing both wide situational awareness at lower magnification and finely-detailed views at higher zoom levels. The eye relief is approximately 90 mm, ensuring comfortable viewing across shooting positions.

The turret system features ultra-fine 0.1 mrad click values, and the internal adjustment ranges exceed 40 mrad, giving the shooter a massive envelope for elevation and windage correction. The scope's innovative "LPI" (Illuminated-Parallax-Integrated) system enhances usability, including left-hand shooter compatibility and more mounting flexibility.

Key Specifications:

Magnification: 6–36×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 7.3–1.3 m @100 m
Exit Pupil: approx. 8.3–1.6 mm
Eye Relief: approx. 90 mm
Transmission: >90%
Click Value: ~0.1 mrad
Length: approx. 390 mm
Weight: approx. 940 g

Designed and manufactured in Germany with highest precision, the 6-36×56 PM II High Performance is ideal for professionals, competition marksmen or hunters seeking top-tier optical clarity, mechanical integrity and flexibility across distances that demand elite performance.

Attributes

- Name: [6-36x56 PM II High Performance LPI TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015886
- Mfr. No.: 163-911-532-G8-E8

NO IMAGE
AVAILABLE

- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537069921

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 6-36x56 PM II High Performance Rifle Scope](#)
- [About Us](#)

Safety Instruction Guide for the 6-36x56 PM II High Performance Rifle Scope

Introduction

Thank you for choosing the 6-36x56 PM II High Performance Rifle Scope from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe use and handling of your product. Please read this document carefully before using the scope.

General Safety Guidelines

- **Product Safety:** This product is designed for safe use in accordance with EU regulations. Ensure you understand how to operate it safely.
- **Enhanced Recalls:** In the event of a safety issue, standardized recall notices will be issued. Always check for updates.
- **Online Shopping:** If purchased online, ensure the seller complies with safety requirements.
- **Special Consumer Focus:** This product is not intended for use by children. Keep out of reach of minors.
- **EU Contact Point:** For safety inquiries, refer to the designated EU contact point provided by the retailer.
- **Rapid Alerts:** Stay informed about product safety through the EU Safety Gate system.

Specific Safety Precautions for Use

- **Avoid Direct Eye Exposure:** Never look directly at the sun or other intense light sources through the scope, as this can cause severe eye damage.
- **Secure Mounting:** Ensure the scope is securely mounted to prevent it from loosening during use.
- **Check for Damage:** Before each use, inspect the scope for any signs of damage or wear. Do not use if damaged.
- **Proper Handling:** Handle the scope with care to avoid dropping or impacting it, which can affect its performance.
- **Use Appropriate Tools:** When adjusting or mounting the scope, use the appropriate tools to prevent damage.
- **Follow Local Laws:** Ensure compliance with local laws and regulations regarding the use of rifle scopes and firearms.

Instructions for Installation and Usage

1. Installation:

- Choose a suitable mounting location on your rifle.
- Use the appropriate rings and base to securely attach the scope to the rifle.
- Ensure the scope is level and properly aligned with the rifle's barrel.
- Tighten all screws and fittings to the manufacturer's specifications.

2. Usage:

- Adjust the magnification as needed using the zoom ring.
- Use the turret system to make precise adjustments for elevation and windage.
- Always check the reticle for clarity and alignment before shooting.
- Maintain a proper shooting stance and ensure a firm grip on the rifle.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the scope and any associated materials in accordance with local regulations.
- **Recycling:** Where possible, recycle packaging materials and components.
- **Hazardous Materials:** If the product contains any hazardous materials, follow local guidelines for safe disposal.

Contact Information for Further Support

For any questions or concerns regarding the use and safety of your 6-36x56 PM II High Performance Rifle Scope, please refer to the contact information provided by your retailer or manufacturer.

Thank you for your attention to these safety instructions. Your safety and the safety of others is our top priority. Enjoy your shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk