

6-36x56 PM II High Performance - 6-36x56 PM II High Performance LPI TREMOR5 1cm ccw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 6-36×56 PM II High Performance from Schmidt and Bender is a benchmark optic engineered for serious medium- to extreme-long-range shooting. With its expansive 6–36× magnification range and a generous 56 mm objective lens, it delivers exceptional clarity, reach and flexibility for demanding applications.

Crafted on a robust 34 mm main tube, the scope is compact in length (approx. 390 mm) and relatively light for its class (around 940 g), yet built with the ruggedness and precision befitting the PM II series. The first-focal-plane (FFP) reticle ensures accurate hold-overs, ranging and subtensions at every magnification level. With a transmission rating of well over 90 %, the optical system offers bright, high-resolution imagery critical for target recognition at extended distances.

Its field of view spans about 7.3–1.3 m @100 m, and the exit pupil ranges from approximately 8.3–1.6 mm, providing both wide situational awareness at lower magnification and finely-detailed views at higher zoom levels. The eye relief is approximately 90 mm, ensuring comfortable viewing across shooting positions.

The turret system features ultra-fine 0.1 mrad click values, and the internal adjustment ranges exceed 40 mrad, giving the shooter a massive envelope for elevation and windage correction. The scope's innovative "LPI" (Illuminated-Parallax-Integrated) system enhances usability, including left-hand shooter compatibility and more mounting flexibility.

Key Specifications:

Magnification: 6–36×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 7.3–1.3 m @100 m
Exit Pupil: approx. 8.3–1.6 mm
Eye Relief: approx. 90 mm
Transmission: >90%
Click Value: ~0.1 mrad
Length: approx. 390 mm
Weight: approx. 940 g

Designed and manufactured in Germany with highest precision, the 6-36×56 PM II High Performance is ideal for professionals, competition marksmen or hunters seeking top-tier optical clarity, mechanical integrity and flexibility across distances that demand elite performance.

Attributes

- Name: [6-36x56 PM II High Performance LPI TREMOR5 1cm ccw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015894
- Mfr. No.: 163-911-552-F1-E8

NO IMAGE
AVAILABLE

- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537066715

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 6-36x56 PM II High Performance Rifle Scope](#)
- [About Us](#)

Safety Instruction Guide for the 6-36x56 PM II High Performance Rifle Scope

Introduction

Thank you for choosing the 6-36x56 PM II High Performance Rifle Scope by Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your rifle scope. Please read this document carefully before using the product.

General Safety Guidelines

- Ensure that the rifle scope is suitable for your specific firearm and intended use.
- Always handle the rifle scope and firearm with care, treating them as if they are loaded.
- Keep the rifle scope out of reach of children and unauthorized users.
- Be aware of your surroundings and ensure a safe shooting environment.
- Regularly inspect the rifle scope for any signs of damage or wear before use.
- Follow all local laws and regulations regarding firearm use and ownership.

Specific Safety Precautions for Use

- Do not look directly at the sun through the scope, as this can cause serious eye damage.
- Ensure that the mounting system is secure to prevent the scope from shifting during use.
- Avoid using the scope in extreme weather conditions that may affect its performance.
- Use the scope only for its intended purpose; do not modify or disassemble it.
- Always use appropriate eye protection when using the rifle scope.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Mount the scope securely using compatible rings and bases.
- Adjust the scope's position for optimal eye relief and comfort.
- Tighten all mounting screws to the manufacturer's specifications.

2. Usage:

- Familiarize yourself with the scope's features and adjustments before shooting.
- Set the magnification to the desired level based on your shooting distance.
- Use the firstfocalplane reticle for accurate holdovers and ranging.
- Adjust the turret system for elevation and windage as needed.
- Maintain a proper shooting stance and ensure a clear line of sight.

Disposal Instructions

- Dispose of the rifle scope responsibly and in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling components where possible.

Contact Information for Further Support

For any questions or concerns regarding the safety and use of your rifle scope, please refer to the

manufacturer's website or contact your local distributor for assistance.

Conclusion

By following these safety guidelines and instructions, you can ensure the safe and effective use of your 6-36x56 PM II High Performance Rifle Scope. Always prioritize safety and responsibility when handling firearms and optical equipment. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk