

6-36x56 PM II High Performance - 6-36x56 PM II High Performance LPI TREMOR5 1cm ccw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 6-36×56 PM II High Performance from Schmidt and Bender is a benchmark optic engineered for serious medium- to extreme-long-range shooting. With its expansive 6–36× magnification range and a generous 56 mm objective lens, it delivers exceptional clarity, reach and flexibility for demanding applications.

Crafted on a robust 34 mm main tube, the scope is compact in length (approx. 390 mm) and relatively light for its class (around 940 g), yet built with the ruggedness and precision befitting the PM II series. The first-focal-plane (FFP) reticle ensures accurate hold-overs, ranging and subtensions at every magnification level. With a transmission rating of well over 90 %, the optical system offers bright, high-resolution imagery critical for target recognition at extended distances.

Its field of view spans about 7.3–1.3 m @100 m, and the exit pupil ranges from approximately 8.3–1.6 mm, providing both wide situational awareness at lower magnification and finely-detailed views at higher zoom levels. The eye relief is approximately 90 mm, ensuring comfortable viewing across shooting positions.

The turret system features ultra-fine 0.1 mrad click values, and the internal adjustment ranges exceed 40 mrad, giving the shooter a massive envelope for elevation and windage correction. The scope's innovative "LPI" (Illuminated-Parallax-Integrated) system enhances usability, including left-hand shooter compatibility and more mounting flexibility.

Key Specifications:

Magnification: 6–36×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 7.3–1.3 m @100 m
Exit Pupil: approx. 8.3–1.6 mm
Eye Relief: approx. 90 mm
Transmission: >90%
Click Value: ~0.1 mrad
Length: approx. 390 mm
Weight: approx. 940 g

Designed and manufactured in Germany with highest precision, the 6-36×56 PM II High Performance is ideal for professionals, competition marksmen or hunters seeking top-tier optical clarity, mechanical integrity and flexibility across distances that demand elite performance.

Attributes

- Name: [6-36x56 PM II High Performance LPI TREMOR5 1cm ccw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015900
- Mfr. No.: 163-911-552-M2-I5

NO IMAGE
AVAILABLE

- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537066739

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 6-36x56 PM II High Performance Rifle Scope](#)
- [About Us](#)

Safety Instruction Guide for the 6-36x56 PM II High Performance Rifle Scope

Introduction

Thank you for choosing the 6-36x56 PM II High Performance Rifle Scope from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your rifle scope. Please read this guide carefully before using the product.

General Safety Guidelines

- **Product Safety:** Always ensure that the rifle scope is used according to the manufacturer's specifications to avoid accidents and injuries.
- **Enhanced Recalls:** Stay informed about any recalls or safety notices related to this product by checking the EU Safety Gate platform regularly.
- **Online Shopping:** If purchased online, ensure that the seller complies with EU safety regulations.
- **Special Consumer Focus:** This product is not intended for use by children. Always supervise its use in environments where children are present.
- **EU Contact Point:** For any safety inquiries, please refer to the contact point provided by the retailer or manufacturer.
- **Rapid Alerts:** Be aware of the Safety Gate system for prompt updates on any unsafe products.

Specific Safety Precautions for Use

- **Avoid Eye Injuries:** Always use protective eyewear when using firearms equipped with this scope.
- **Secure Mounting:** Ensure that the scope is securely mounted to the firearm to prevent it from loosening or detaching during use.
- **Check for Damage:** Regularly inspect the scope for any signs of damage or wear. Do not use the scope if it is damaged.
- **Proper Handling:** Handle the scope with care to avoid scratches or damage to the lenses and housing.
- **Avoid Extreme Conditions:** Do not expose the scope to extreme temperatures or humidity, as this may affect its performance.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded before mounting the scope.
- Use appropriate mounting rings compatible with a 34 mm main tube.
- Align the scope in a straight line with the barrel for accurate aiming.
- Tighten the mounting rings securely but avoid overtightening, which could damage the scope.

2. Usage:

- Adjust the magnification as needed using the zoom ring.
- Use the firstfocalplane reticle for accurate holdovers and ranging at any magnification.
- Make adjustments using the turret system, ensuring to account for windage and elevation corrections.
- Maintain a comfortable eye relief of approximately 90 mm for optimal viewing.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the scope responsibly, following local regulations for electronic waste and optical devices.
- **Recycling:** If possible, recycle components of the scope, such as metal and glass, at designated recycling centers.

Contact Information for Further Support

For further assistance or inquiries regarding the 6-36x56 PM II High Performance Rifle Scope, please consult the retailer or manufacturer from whom you purchased this product. They can provide you with the necessary support and information.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 6-36x56 PM II High Performance Rifle Scope. Thank you for your attention to safety, and happy shooting!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk