

6-36x56 PM II High Performance - 6-36x56 PM II High Performance LPI P5FL 0,05 mrad ccw MT II MTC LT / DT II+ ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 6-36×56 PM II High Performance from Schmidt and Bender is a benchmark optic engineered for serious medium- to extreme-long-range shooting. With its expansive 6–36× magnification range and a generous 56 mm objective lens, it delivers exceptional clarity, reach and flexibility for demanding applications.

Crafted on a robust 34 mm main tube, the scope is compact in length (approx. 390 mm) and relatively light for its class (around 940 g), yet built with the ruggedness and precision befitting the PM II series. The first-focal-plane (FFP) reticle ensures accurate hold-overs, ranging and subtensions at every magnification level. With a transmission rating of well over 90 %, the optical system offers bright, high-resolution imagery critical for target recognition at extended distances.

Its field of view spans about 7.3–1.3 m @100 m, and the exit pupil ranges from approximately 8.3–1.6 mm, providing both wide situational awareness at lower magnification and finely-detailed views at higher zoom levels. The eye relief is approximately 90 mm, ensuring comfortable viewing across shooting positions.

The turret system features ultra-fine 0.1 mrad click values, and the internal adjustment ranges exceed 40 mrad, giving the shooter a massive envelope for elevation and windage correction. The scope's innovative "LPI" (Illuminated-Parallax-Integrated) system enhances usability, including left-hand shooter compatibility and more mounting flexibility.

Key Specifications:

Magnification: 6–36×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 7.3–1.3 m @100 m
Exit Pupil: approx. 8.3–1.6 mm
Eye Relief: approx. 90 mm
Transmission: >90%
Click Value: ~0.1 mrad
Length: approx. 390 mm
Weight: approx. 940 g

Designed and manufactured in Germany with highest precision, the 6-36×56 PM II High Performance is ideal for professionals, competition marksmen or hunters seeking top-tier optical clarity, mechanical integrity and flexibility across distances that demand elite performance.

Attributes

- Name: [6-36x56 PM II High Performance LPI P5FL 0,05 mrad ccw MT II MTC LT / DT II+ ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015901
- Mfr. No.: 163-911-642-I5-H5

NO IMAGE
AVAILABLE

- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065947

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 6-36x56 PM II High Performance](#)
- [About Us](#)

Safety Instruction Guide for the 6-36x56 PM II High Performance

Introduction

Thank you for choosing the 6-36x56 PM II High Performance from Schmidt and Bender. This product is designed for serious medium to extreme longrange shooting. To ensure your safety and the optimal performance of your scope, please read and follow this safety instruction guide carefully.

General Safety Guidelines

- **Product Safety:** This product is designed to be safe for use. However, improper handling can lead to accidents. Always handle with care.
- **Enhanced Recalls:** Stay informed about any product recalls. Standardized recall notices will provide information on dangerous products.
- **Online Shopping Protections:** If purchased online, ensure that the seller complies with safety requirements as per EU regulations.
- **Special Consumer Focus:** Extra care should be taken when children are present. Keep this product out of reach of children.
- **EU Contact Point:** For any safety inquiries, ensure you have access to an EUbased contact.
- **Rapid Alerts:** Keep updated on unsafe products through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always use the scope according to the manufacturer's specifications.
- Ensure the scope is securely mounted to the rifle to prevent accidents.
- Do not look directly at the sun through the scope, as this can cause serious eye damage.
- Check the scope for any signs of damage before use. If damaged, do not use and contact support.
- Use the scope only for its intended purpose; misuse can lead to accidents.
- Maintain a safe distance from others when firing to prevent injury from ricochets or misfires.
- Always ensure the rifle is pointed in a safe direction when adjusting or using the scope.
- Ensure that the area is clear of people and obstacles before taking a shot.

Instructions for Installation and Usage

1. Installation:

- Ensure you have the necessary tools for mounting the scope.
- Follow the manufacturer's instructions for mounting to ensure secure attachment.
- Check that the scope is level and aligned with the rifle barrel.

2. Usage:

- Adjust the magnification setting according to your shooting requirements.
- Use the firstfocalplane reticle for accurate holdovers at all magnification levels.
- Make adjustments to the turret system as needed for elevation and windage.
- Ensure your eye relief is set correctly for comfortable viewing.
- Use the LPI system for enhanced usability, especially if you are a lefthanded shooter.

Disposal Instructions

- Dispose of the product responsibly at the end of its life cycle.
- Follow local regulations for disposal of optical equipment.

- Do not dispose of the product in regular household waste.

Contact Information for Further Support

For any questions or concerns regarding the 6-36x56 PM II High Performance scope, please refer to the manufacturer's contact information provided with your product.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 6-36x56 PM II High Performance scope. Thank you for your attention to these important safety guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk